

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number
WO 2005/086627 A2

(51) International Patent Classification: **Not classified**

#203, Los Angeles, CA 90066 (US). **HE, Jun** [CN/CN];
Fudan University, Shanghai (CN).

(21) International Application Number:
PCT/US2004/040368

(74) Agent: **OLDENKAMP, David, J.**; Shapiro & Dupont
LLP, 233 Wilshire Boulevard, Suite 700, Santa Monica, CA
90401 (US).

(22) International Filing Date: 1 December 2004 (01.12.2004)

(25) Filing Language: English

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(26) Publication Language: English

(30) Priority Data:
60/527,041 3 December 2003 (03.12.2003) US

(71) Applicant (*for all designated States except US*): **THE
REGENTS OF THE UNIVERSITY OF CALIFORNIA**
[US/US]; 1111 Franklin Street, 12th Floor, Oakland, CA
94607-5200 (US).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **YANG, Yang**
[US/US]; 13730 Bayliss Road, Los Angeles, CA 90095
(US). **MA, Liping** [CN/US]; 3290 Sawtelle Boulevard

[Continued on next page]

(54) Title: THREE-TERMINAL ELECTRICAL BISTABLE DEVICES



(a)



(b)

(57) Abstract: A three terminal electrical bistable device that includes a tri-layer composed of an electrically conductive mixed layer sandwiched between two layers of low conductivity organic material that is interposed between a top electrode and a bottom electrode. The conducting mixed layer serves as the middle electrode. The device includes two memory cells composed of electrode/organic layer/mixed layer, where the interfaces between the electrically conductive mixed layer and the low conductivity organic layer exhibit bistable behavior.



WO 2005/086627 A2



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *without international search report and to be republished upon receipt of that report*